



SAE 10W40

140100701



SEMISYNTHETIC ACTIVE SM/CF/EC SAE 10W40

This product is a high quality semi-synthetic long-life engine oil. This product can be used for the lubrication of all 4-Stroke gasoline and diesel engines, which makes it perfect oil for the whole fleet. It is also suitable for vehicles that operate with a direct fuel injection. The total engine

protection of this lubricant ensures outstanding engine cleanliness and it is very suitable for cold starts and Start-Stop traffic. This product has the API SM specification but can also be used where older API specifications are applicable like SJ and SL.

GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,868
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	95,4
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	14,1
Viscosity Index	ASTM D2270		152
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	8,3
Pour point	ASTM D6892	°C	-36
Flash point	ASTM D92	°C	220
Sulphated ash content	ASTM D874	%	1
CCS viscosity @ -15 °C	ASTM D5293	mPa.s	
CCS viscosity @ -20 °C	ASTM D5293	mPa.s	
CCS viscosity @ -25 °C	ASTM D5293	mPa.s	6500
CCS viscosity @ -30 °C	ASTM D5293	mPa.s	
CCS viscosity @ -35 °C	ASTM D5293	mPa.s	

All data on this technical data sheet is indicative only.

Specifications

- ▷ ACEA A3/B4
- ▷ API SM/CF
- ▷ MB 226.5
- ▷ MB 229.3
- ▷ RENAULT RN 0700
- ▷ RENAULT RN 0710
- ▷ VW 502 00
- ▷ VW 505 00