

SAE 0W40

140101501

GOLD PLATINUM SN/CF SAE 0W40

This product is a very advanced full synthetic engine oil that has been developed for gasoline and diesel engines. The full synthetic technology in this engine oil is several times more able to effectively remove sludge and dirt from engines than a mineral oil. This product ensures that your engine is driving like new in all driving conditions. This product has a very rapid engine protection start up,

which makes it perfect for short distance driving and start-stop driving. Also the specifically designed additive package ensures that dirty engines are cleaned tremendously. This product is very suitable for engines that include turbo-chargers, direct injections diesels and Hybrids. Please note that this product is not suitable for vehicles with DPF filters.

GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,844
Kinematic viscosity @ 40 °C	ASTM D445	mm²/s	80,1
Kinematic viscosity @ 100 °C	ASTM D445	mm²/s	13,8
Viscosity Index	ASTM D2270		178
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	10,1
Pour point	ASTM D6892	°C	-57
Flash point	ASTM D92	°C	220
Sulphated ash content	ASTM D874	%	1,09
CCS viscosity @ -15 °C	ASTM D5293	mPa.s	
CCS viscosity @ -20 °C	ASTM D5293	mPa.s	
CCS viscosity @ -25 °C	ASTM D5293	mPa.s	
CCS viscosity @ -30 °C	ASTM D5293	mPa.s	
CCS viscosity @ -35 °C	ASTM D5293	mPa.s	6040

All data on this technical data sheet is indicative only.

Specifications

- ▷ ACEA A3/B4
- ▷ API SN
- ▷ BMW LONGLIFE-01
- ▷ MB 229.5
- ▷ PORSCHE A40
- ▷ RENAULT RN 0700
- ▷ RENAULT RN 0710
- ▷ VW 502 00
- ▷ VW 505 00