



SAE 10W60

140101901



GOLD PLATINUM SN/CF SAE 10W60

This product is a very advanced semi-synthetic engine oil. This product is suitable in four-stroke petrol and diesel engines for passenger cars, and light vans. It can be used in direct-injection diesel engines such as common rail, HDI, CDI etc. This product is formulated with a good all year

round additive package and can be used in a wide variety of vehicles. One of the added values to this 10W60 grades compared to other grades is that it is particularly suitable in extreme operating conditions. It ensures a flexible combination of high and low temperature protection.

GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,866
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	171
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	24,5
Viscosity Index	ASTM D2270		175
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	9,6
Pour point	ASTM D6892	°C	-36
Flash point	ASTM D92	°C	238
Sulphated ash content	ASTM D874	%	1,1
CCS viscosity @ -15 °C	ASTM D5293	mPa.s	
CCS viscosity @ -20 °C	ASTM D5293	mPa.s	
CCS viscosity @ -25 °C	ASTM D5293	mPa.s	6700
CCS viscosity @ -30 °C	ASTM D5293	mPa.s	
CCS viscosity @ -35 °C	ASTM D5293	mPa.s	

Specifications

- ▷ ACEA A3/B4
- ▷ API SN/CF
- ▷ VW 501 01
- ▷ VW 505 00

All data on this technical data sheet is indicative only.