

SAE 5W30

140104901

MOLINOL PAO SAE 5W30

This is a full synthetic engine oil that is formulated with our PAO (Poly Alpha Olefin) technology. This product is suitable for passenger cars equipped with gasoline, diesel and LPG engines and that have after treatment devices and diesel particle filters. The PAO base oils used in this formulation ensure excellent low temperature fluidity, oxidation stability and thermal stability. The PAO synthetic base

stocks offer low volatility required to perform the harshest temperatures. This product has exceptional properties compared to normal full synthetic engine oils and meets a variety of specifications. This product can be used perfectly in applications that are in need of demanding properties like racing and sporty driving.

GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,853
Kinematic viscosity @ 40 °C	ASTM D445	mm²/s	70
Kinematic viscosity @ 100 °C	ASTM D445	mm²/s	11,6
Viscosity Index	ASTM D2270		161
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	6,3
Pour point	ASTM D6892	°C	-39
Flash point	ASTM D92	°C	230
Sulphated ash content	ASTM D874	%	0,7
CCS viscosity @ -15 °C	ASTM D5293	mPa.s	
CCS viscosity @ -20 °C	ASTM D5293	mPa.s	
CCS viscosity @ -25 °C	ASTM D5293	mPa.s	
CCS viscosity @ -30 °C	ASTM D5293	mPa.s	5600
CCS viscosity @ -35 °C	ASTM D5293	mPa.s	

All data on this technical data sheet is indicative only.

Specifications

- ▷ ACEA C2
- ▷ ACEA C3
- ▷ API SN
- ▷ BMW LONGLIFE-04
- ▷ MB 229.51
- ▷ PORSCHE C30
- ▷ VW 504 00
- ▷ VW 507 00