

SAE 0W30

140105301

GOLD SYNTHESIS SM/CF/EC SAE 0W30

This is a full synthetic engine oil that offers excellent fluidity at low temperatures. A result of this is that this product can be used perfectly in engines that have start-stop mechanisms or vehicles that are used for short-distance

driving. This product can be used in all 4-stroke engines, four-valve, turbocharges, and 4-stroke diesel engines with or without turbo. Please note that this product is not suitable in vehicles that have diesel particle filters.

GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,844
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	66
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	11,9
Viscosity Index	ASTM D2270		179
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	10,1
Pour point	ASTM D6892	°C	-51
Flash point	ASTM D92	°C	220
Sulphated ash content	ASTM D874	%	1,1
CCS viscosity @ -15 °C	ASTM D5293	mPa.s	
CCS viscosity @ -20 °C	ASTM D5293	mPa.s	
CCS viscosity @ -25 °C	ASTM D5293	mPa.s	
CCS viscosity @ -30 °C	ASTM D5293	mPa.s	
CCS viscosity @ -35 °C	ASTM D5293	mPa.s	5600

All data on this technical data sheet is indicative only.

Specifications

- ▷ ACEA A3/B4
- ▷ API SM
- ▷ BMW LONGLIFE-01
- ▷ MB 229.3
- ▷ VW 502 00
- ▷ VW 505 00