

SAE 0W30

140105401



INNOVATION C2 SAE 0W30

This is a full synthetic engine oil that has been developed for the EURO 6 TDCI Duratorq engines in Ford engines after 2004. This product includes one of the latest technology Viscosity Index Improvers. This ensures that this product lasts very long before it needs oil changes. This product is developed for mandatory use in the newest EURO 6 TDCI

Duratorq Ford engines. This product is also usable for other passenger car engines requiring a 0W30 viscosity grade and the ACEA C2 performance. This product provides total engine protection and can be used in start-stop driving and short distance driving because of its excellent cold start properties.

GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,847
Kinematic viscosity @ 40 °C	ASTM D445	mm²/s	45,6
Kinematic viscosity @ 100 °C	ASTM D445	mm²/s	9,4
Viscosity Index	ASTM D2270		196
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	7,8
Pour point	ASTM D6892	°C	-48
Flash point	ASTM D92	°C	210
Sulphated ash content	ASTM D874	%	0,79
CCS viscosity @ -15 °C	ASTM D5293	mPa.s	
CCS viscosity @ -20 °C	ASTM D5293	mPa.s	
CCS viscosity @ -25 °C	ASTM D5293	mPa.s	
CCS viscosity @ -30 °C	ASTM D5293	mPa.s	
CCS viscosity @ -35 °C	ASTM D5293	mPa.s	5600

All data on this technical data sheet is indicative only.

Specifications

- ▷ ACEA C2
- ▷ FORD WSS-M2C950-A
- ▷ JAGUAR STJLR.03.5007