

SAE 0W30

140105501



INNOVATION C2 LL-12 SAE 0W30

This is a full synthetic engine oil that is very suitable for vehicles that need to meet the BMW II-12 FE specification. This product can be used in vehicles that require an ACEA C2 specification. This product is mandatory in the newest

BMW gasoline and diesel engines. It provides excellent fuel economy results and can be used in start-stop driving as well as long distance driving.

GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,841
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	54
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	9,8
Viscosity Index	ASTM D2270		169
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-57
Flash point	ASTM D92	°C	225
Sulphated ash content	ASTM D874	%	0,8
CCS viscosity @ -15 °C	ASTM D5293	mPa.s	
CCS viscosity @ -20 °C	ASTM D5293	mPa.s	
CCS viscosity @ -25 °C	ASTM D5293	mPa.s	
CCS viscosity @ -30 °C	ASTM D5293	mPa.s	
CCS viscosity @ -35 °C	ASTM D5293	mPa.s	5400

All data on this technical data sheet is indicative only.

Specifications

- ▷ ACEA C2
- ▷ BMW LONGLIFE-12 FE