

SAE 50

140200501

LOGISTIC TRUCK CF-4 SAE 50

This is a high quality mineral heavy duty truck engine oil suitable for naturally aspirated or supercharged diesel and gasoline engines. This product is recommended for fixed diesel engines, and mixed fleets of trucks and cars.

The additive technology used in these products ensure long and reliable protection of all the engine parts. These products meet a variety of OEM specifications. This product is very suitable for the use in warmer climates.

| GRADE | METHOD | UNIT | VALUE |
|------------------------------|------------|--------------------|-------|
| Density @ 15 °C | ASTM D4052 | kg/l | 0,9 |
| Kinematic viscosity @ 40 °C | ASTM D445 | mm ² /s | 194 |
| Kinematic viscosity @ 100 °C | ASTM D445 | mm ² /s | 17,6 |
| Viscosity Index | ASTM D2270 | | 100 |
| B.N. (HCL04 method) | ASTM D2896 | mg KOH/g | 7,6 |
| Pour point | ASTM D6892 | °C | -15 |
| Flash point | ASTM D92 | °C | 244 |
| Sulphated ash content | ASTM D874 | % | 1,1 |
| CCS viscosity @ -15 °C | ASTM D5293 | mPa.s | |
| CCS viscosity @ -20 °C | ASTM D5293 | mPa.s | |
| CCS viscosity @ -25 °C | ASTM D5293 | mPa.s | |
| CCS viscosity @ -30 °C | ASTM D5293 | mPa.s | |

All data on this technical data sheet is indicative only.

Specifications

- ▷ API CF-4/SG
- ▷ MB 227.0
- ▷ MIL-L-2104 E
- ▷ MIL-L-46152 E