

SAE 10W40

140202501

PROFESSIONAL CJ-4 E7/E9 SAE 10W40

This is a LOW SAPS semi-synthetic heavy duty engine oil that can be used in all four-stroke diesel engines. Compared to more traditional heavy duty engine oils this product significantly reduces pollution and exhaust emissions.

It ensures full after treatment protection and it meets the EURO V, EURO VI and EURO III emission norms. The newest additives are used in this product that ensure long lifetime and excellent engine protection.

GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,865
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	91
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	13,9
Viscosity Index	ASTM D2270		156
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-39
Flash point	ASTM D92	°C	225
Sulphated ash content	ASTM D874	%	1
CCS viscosity @ -15 °C	ASTM D5293	mPa.s	
CCS viscosity @ -20 °C	ASTM D5293	mPa.s	
CCS viscosity @ -25 °C	ASTM D5293	mPa.s	5700
CCS viscosity @ -30 °C	ASTM D5293	mPa.s	

All data on this technical data sheet is indicative only.

Specifications

- ▷ ACEA E7
- ▷ ACEA E9
- ▷ API CJ-4/SM
- ▷ CATERPILLAR ECF-2
- ▷ CATERPILLAR ECF-3
- ▷ CUMMINS CES 20081
- ▷ DEUTZ DQC III-10 LA
- ▷ MACK EO-O PREMIUM PLUS
- ▷ MAN M3575
- ▷ MB 228.31
- ▷ RENAULT RLD-3
- ▷ VOLVO VDS-4