

SAE 5W30

140203101



DURABLE CJ-4 E4/E6/E7/E9 SAE 5W30

This is a full synthetic heavy duty engine oil that meets the highest performance standards for the newest large truck fleets. This product is recommended for EURO V and EURO VI engines. This product enables very high levels of fuel economy and protects the engine all year round for very

long interval ranges. This product can be used in vehicles that are equipped with after treatment devices (EGR, SCR, DPF etc.). This is one of the best products in the market for maintaining the newer truck portfolio.

GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,856
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	68,9
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	11,8
Viscosity Index	ASTM D2270		168
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	12,8
Pour point	ASTM D6892	°C	
Flash point	ASTM D92	°C	
Sulphated ash content	ASTM D874	%	
CCS viscosity @ -15 °C	ASTM D5293	mPa.s	
CCS viscosity @ -20 °C	ASTM D5293	mPa.s	
CCS viscosity @ -25 °C	ASTM D5293	mPa.s	
CCS viscosity @ -30 °C	ASTM D5293	mPa.s	

All data on this technical data sheet is indicative only.

Specifications

- ▷ ACEA E4
- ▷ ACEA E6
- ▷ ACEA E7
- ▷ ACEA E9
- ▷ API CJ-4
- ▷ API SN
- ▷ CATERPILLAR ECF-3
- ▷ CUMMINS CES 20081
- ▷ DETROIT DIESEL 93K218
- ▷ DEUTZ DQC IV-10 LA
- ▷ JASO DH-2
- ▷ MACK EO-M PLUS
- ▷ MACK EO-N PREMIUM PLUS
- ▷ MACK EO-O PREMIUM PLUS
- ▷ MAN M3271-1
- ▷ MAN M3477
- ▷ MAN M3575
- ▷ MAN M3677