

LS 2T

140300301

SCOOTER LS 2T

This is a 2-stroke engine oil that has been made from the most excellent semi-synthetic base oils. Additives are added that ensure complete engine lubrication. It reduces deposits in the combustion chamber and flushing ports. Also, it contains very high cleaning properties in order to clean the spark plugs. This ensures that the engine will

keep its power over time. The formulation ensures that there is low to little smoke formation and this product is perfectly suitable for high-speed as well as heavily loaded air-cooled 2-stroke engines. This product can also be used in engines with water cooling/radiator cooling.

GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,866
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	64,6
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	9,5
Viscosity Index	ASTM D2270		129
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	1,4
Pour point	ASTM D6892	°C	-24
Flash point COC	ASTM D92	°C	116
Flash Point PM		°C	
Sulphated ash content	ASTM D874	%	0,14

All data on this technical data sheet is indicative only.

Specifications

- ▷ 2-Stroke DFI
- ▷ API TC
- ▷ Global GD
- ▷ Husqvarna 272
- ▷ ISO L-EGD
- ▷ JASO FD