

PIA 2T

140300401

## SCOOTER PIA 2T

This is a synthetic 2-stroke engine oil that is formulated to ensure complete engine maintenance and cleaning. This product reduces the deposits in the combustion chamber and flushing ports, and keeps the spark plugs clean and

ensures that engine power is restored. This self-mixing two-stroke oil is extremely suitable for use in high-speed and heavily loaded air-cooled two-stroke engines and especially suitable for use in kart and racing engines.



GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,88
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	44
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	8,8
Viscosity Index	ASTM D2270		167
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	6,6
Pour point	ASTM D6892	°C	-36
Flash point COC	ASTM D92	°C	
Flash Point PM		°C	78
Sulphated ash content	ASTM D874	%	0,26

*All data on this technical data sheet is indicative only.*

## Specifications

- ▷ 2-Stroke DFI
- ▷ API TC
- ▷ Husqvarna 272
- ▷ ISO L-EGD
- ▷ JASO FD