

FD 2T

140300601



## MOLINOL SYNTHETIC FD 2T

This is a 2-stroke engine oil that has been made from the most excellent full-synthetic base oils. Additives are added that ensure complete engine lubrication. It reduces deposits in the combustion chamber and flushing ports. Also it contains very high cleaning properties in order to clean the spark plugs. This ensures that the engine will

keep its power over time. The formulation ensures that there is low to little smoke formation and this product is perfectly suitable for high-speed as well as heavily loaded air-cooled 2-stroke engines. This product can also be used in engines with water cooling/radiator cooling. Dosage: 2 to 4% according to manufacturers recommendation.

GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,875
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	72,2
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	10,8
Viscosity Index	ASTM D2270		138
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	1,2
Pour point	ASTM D6892	°C	-48
Flash point COC	ASTM D92	°C	100
Flash Point PM		°C	
Sulphated ash content	ASTM D874	%	

*All data on this technical data sheet is indicative only.*

## Specifications

- ▷ API TC
- ▷ ISO L-EGD
- ▷ JASO FC
- ▷ JASO FD