

2T

140300801

## MOLINOL SNOW 2T

This is a synthetic lubricant that is specifically designed for the use in snow scooters and snowmobiles. The product is developed to function particularly well in cold temperature climates. We have added our ester technology that ensures a strong lubricating film and an excellent protection at high operating temperatures. It is pre-diluted for easy mixing, has a very low pour point and ensures

free flowing of fuel, even at very low temperatures. This is primarily suitable for the latest generation of 2-cycle snowmobiles equipped with fuel injection systems (EFI or DFI) and/or exhaust power valve engines. It is recommended as an injector oil or at a 50:1 ratio in carburetted or direct fuel injection systems.

GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,857
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	42,7
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	7,9
Viscosity Index	ASTM D2270		158
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	5,1
Pour point	ASTM D6892	°C	-42
Flash point COC	ASTM D92	°C	104
Flash Point PM		°C	
Sulphated ash content	ASTM D874	%	0

*All data on this technical data sheet is indicative only.*

## Specifications

- ▷ API Approval FC
- ▷ API Approval TC
- ▷ API TC
- ▷ JASO FC
- ▷ NMMA TC-W3