

SAE 10W40

140400101

MOTO FORMULA 4T SAE 10W40

This is a motorcycle and scooter engine oil that is made out of the finest mineral base oils. This product is very suitable for (city) touring, racing a cross motors. This product is developed with ester technology additives that ensure that there is optimal friction prevention. This product can be used in vehicles where the API SF/SG oil is prescribed. With the development of this product, it has been formu-

lated in a way that it offers excellent protection to the gearbox and wet disk clutches. Also, it is very suitable for daily city work-life traffic and the cold start properties ensure optimal engine protection even at cold starts. The JASO MA specification on this product ensures that it can be used in all 4-stroke motorcycle and scooter engines with one oil system for engine, gearbox and wet clutch.

GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,855
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	98,4
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	15,1
Viscosity Index	ASTM D2270		161
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	6,3
Pour point	ASTM D6892	°C	-36
Flash point	ASTM D92	°C	224
Sulphated ash content	ASTM D874	%	
CCS viscosity @ -15 °C	ASTM D5293	mPa.s	
CCS viscosity @ -20 °C	ASTM D5293	mPa.s	
CCS viscosity @ -25 °C	ASTM D5293	mPa.s	4930
CCS viscosity @ -30 °C	ASTM D5293	mPa.s	

All data on this technical data sheet is indicative only.

Specifications

- ▷ API SG
- ▷ JASO MA