

SAE 25W50

140400501

## MOTO FORMULA 4T SAE 25W50

This is a motorcycle and scooter engine oil that is made out of the finest mineral base oils. This product is very suitable for (city) touring, racing a cross motors. This product is developed with ester technology additives that ensure that there is optimal friction prevention. This product can be used in vehicles where the API SL oil is prescribed. With the development of this product, it has been formulated

in a way that it offers excellent protection to the gearbox and wet disk clutches. Also, it is very suitable for daily city work-life traffic and the cold start properties ensure optimal engine protection even at cold starts. The JASO MA specification on this product ensures that it can be used in all 4-stroke motorcycle and scooter engines with one oil system for engine, gearbox and wet clutch.

| GRADE                        | METHOD     | UNIT               | VALUE |
|------------------------------|------------|--------------------|-------|
| Density @ 15 °C              | ASTM D4052 | kg/l               | 0,894 |
| Kinematic viscosity @ 40 °C  | ASTM D445  | mm <sup>2</sup> /s | 218   |
| Kinematic viscosity @ 100 °C | ASTM D445  | mm <sup>2</sup> /s | 19,9  |
| Viscosity Index              | ASTM D2270 |                    | 105   |
| B.N. (HCL04 method)          | ASTM D2896 | mg KOH/g           | 5,9   |
| Pour point                   | ASTM D6892 | °C                 | -24   |
| Flash point                  | ASTM D92   | °C                 | 258   |
| Sulphated ash content        | ASTM D874  | %                  |       |
| CCS viscosity @ -15 °C       | ASTM D5293 | mPa.s              |       |
| CCS viscosity @ -20 °C       | ASTM D5293 | mPa.s              |       |
| CCS viscosity @ -25 °C       | ASTM D5293 | mPa.s              |       |
| CCS viscosity @ -30 °C       | ASTM D5293 | mPa.s              |       |

*All data on this technical data sheet is indicative only.*

## Specifications

- ▷ API SG
- ▷ JASO MA