

SAE 10W40

140400601

MOTO SYNTHESIS 4T SAE 10W40

This is an advanced generation of semi-synthetic 4-stroke motorcycle and scooter engine oils. It can be used for both incidental traffic vehicles as well as daily-use vehicles. This product has been based on a formulation that ensures extreme pressure additives in order to maintain

the gearbox optimally. It prevents the wet clutches from slipping and the dispersant and detergents that are added ensure optimal cleanliness. This product can be used in city traffic as well as highway traffic and can be used in all types of motorcycles, quads, 4-stroke scooters.

GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,855
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	101
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	15
Viscosity Index	ASTM D2270		156
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	7,7
Pour point	ASTM D6892	°C	-30
Flash point	ASTM D92	°C	210
Sulphated ash content	ASTM D874	%	0,94
CCS viscosity @ -15 °C	ASTM D5293	mPa.s	
CCS viscosity @ -20 °C	ASTM D5293	mPa.s	
CCS viscosity @ -25 °C	ASTM D5293	mPa.s	5560
CCS viscosity @ -30 °C	ASTM D5293	mPa.s	

All data on this technical data sheet is indicative only.

Specifications

- ▷ API SL
- ▷ JASO MA
- ▷ JASO MA2