

SAE 10W30

140500401



RACING ULTIMATE SAE 10W30

This product can best be used in vehicles that operate under very demanding situations like sports and rally racing. This is a full synthetic engine oil that has been selected out of the best base oils and additives. These base oils naturally contain a high viscosity index. Also high quality

European additives were added in order to ensure that this engine oil has excellent resistance against shearing, high resistance against ageing, excellent lubricating film at cold and high temperatures and a very high anti-corrosion and anti-foaming effect.

GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,878
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	54,8
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	9,73
Viscosity Index	ASTM D2270		164
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	10,3
Pour point	ASTM D6892	°C	
Flash point	ASTM D92	°C	230
Sulphated ash content	ASTM D874	%	1,33
CCS viscosity @ -25 °C	ASTM D5293	mPa.s	2360
CCS viscosity @ -30 °C	ASTM D5293	mPa.s	
CCS viscosity @ -35 °C	ASTM D5293	mPa.s	

All data on this technical data sheet is indicative only.

Specifications

- ▷ ACEA A3/B4
- ▷ API SH/CF
- ▷ API SN/CF