

SAE 80W90

140600701



MOLINOL GEAR GL-4 SAE 80W90

This is a high quality mineral gear oil that has been specifically developed for extreme pressure circumstances and meets that GL-4 specification. The anti-friction additive packages that are used in this product ensure easy shifting. This product is specifically developed to avoid cor-

rosion of copper alloys and can be used in syncromesh gearboxes, transfer boxes, mechanical steering controls and most rear axles. The Anti-wear properties of this products ensure long transmission life.

GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,892
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	
Viscosity Index	ASTM D2270		98
Pour point	ASTM D6892	°C	-30
Flash point	ASTM D92	°C	224
CCS viscosity @ -12 °C	ASTM D2983	mPa.s	
CCS viscosity @ -26 °C	ASTM D2983	mPa.s	
CCS viscosity @ -40 °C	ASTM D2983	mPa.s	
Copper Corrosion	ASTM D130		1A

All data on this technical data sheet is indicative only.

Specifications

- ▷ API GL-4
- ▷ MIL MIL-L-2105