

SAE 75W90

140601201

MOLINOL GEAR GL-4 + SAE 75W90

This is a full synthetic manual gear oil with the GL-4 + specification. This product significantly improves the gear shifting and ensures easy gear shifting at high temperatures. This product is specifically developed for gearboxes

with integrated differentials of front-wheel driven vehicles. This product has an excellent thermal and oxidation stability and significantly extends the transmission life.



GRADE	METHOD	UNIT	VALUE
Density @ 15 °C	ASTM D4052	kg/l	0,858
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	
Viscosity Index	ASTM D2270		206
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	200
CCS viscosity @ -12 °C	ASTM D2983	mPa.s	
CCS viscosity @ -26 °C	ASTM D2983	mPa.s	
CCS viscosity @ -40 °C	ASTM D2983	mPa.s	110000
Copper Corrosion	ASTM D130		

All data on this technical data sheet is indicative only.

Specifications

- ▷ API GL-4 +
- ▷ BMW MTF LT-4
- ▷ FORD WSD-M2C200-D
- ▷ MIL MIL-L-2105
- ▷ VW 501 50