

AUTOMATIC TRANSMISSION FLUIDS



MOLINOL®
PREMIUM GERMAN LUBRICANTS

UNIVERSAL
DEX 2

140700101



MOLINOL ATF UNIVERSAL DEX 2

This ATF II-D is an Automatic Transmission Fluid that is suitable for most passenger cars, forklifts, trucks and buses. It can also be used in power steering systems, torque converters, change gearboxes, fluid clutches and non-complicated hydraulic systems. The high viscosity index offers

resistance against foaming and corrosion. This automatic transmission fluid also has a very low pour point ensuring easy shifting at cold starts. NOTE: This ATF II-D is not suitable for automatic transmissions where a Ford M2C33 F/G specification is recommended.

GRADE	METHOD	UNIT	VALUE
Colour	Visual		Red
Density @ 15 °C	ASTM D4052	kg/l	0,856
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	
Viscosity Index	ASTM D2270		170
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	3
Pour point	ASTM D6892	°C	-39
Flash point	ASTM D92	°C	
CCS viscosity @ -40 °C	ASTM D5293	mPa.s	

Specifications

- ▷ ALLISON C4
- ▷ Ford M2C-138CJ
- ▷ FORD MERCON
- ▷ GM 6137-M
- ▷ GM DEXRON II-D
- ▷ MAN 339 TYP V1
- ▷ MAN 339 TYP Z1
- ▷ MB 236.5
- ▷ MB 236.7
- ▷ VOITH H55.6335xx
- ▷ ZF TE-ML 03D
- ▷ ZF TE-ML 04D
- ▷ ZF TE-ML 09
- ▷ ZF TE-ML 11A
- ▷ ZF TE-ML 14A
- ▷ ZF TE-ML 17C

All data on this technical data sheet is indicative only.