

AUTOMATIC TRANSMISSION FLUIDS



MOLINOL®
PREMIUM GERMAN LUBRICANTS

UNIVERSAL
DEX VI

140700701



MOLINOL ATF UNIVERSAL DEX VI

This ATF VI is an all-round low viscosity Automatic Transmission Fluid. It is developed particularly for automatic transmissions that require low viscosity automatic transmission fluids. This ATF VI ensures easy shifting under all operating temperatures and can be used in a wide temperature

range because of its low pour point. Also, this ATF VI easily meets prescribed intervals because of its excellent oxidation and thermal stability. This product cannot be used in DTC's and CVT's or when an oil with Ford Type F/G is prescribed.

GRADE	METHOD	UNIT	VALUE
Colour	Visual		
Density @ 15 °C	ASTM D4052	kg/l	0,847
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	
Viscosity Index	ASTM D2270		151
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	
CCS viscosity @ -40 °C	ASTM D5293	mPa.s	

All data on this technical data sheet is indicative only.

Specifications

- ▷ GM DEXRON VI
- ▷ Mercon LV
- ▷ MB 236.1/236.5/236.7/
236.8/236.9/236.41
- ▷ VAG G-055-
025/G-052-162
- ▷ Aisin Warner JWS
3309/3324(W/S)
- ▷ Allison TES 228 C3/C4
- ▷ BMW
ETL7045/7045E/8072B/
LA2634
- ▷ Mini Cooper T-IV
- ▷ Chrysler Dodge Mopar
AS68RC (Type IV)
- ▷ Chrysler Dodge Mopar
ATF+/-2/+3/+4
- ▷ Fiat Type IV
- ▷ Ford Mercon/WSS-
M2C138-CJ/166-H/922-