

AUTOMATIC TRANSMISSION FLUIDS



ZF 6

140701301

MOLINOL ATF ZF 6

This is a full synthetic automatic transmission fluid that has been specifically developed for the ZF 6 speed automatic transmissions. They are mainly intended for the ZF 6 speed transmissions for the BMW group, Jaguar and Land

Rover, but it can also be used in a variety of another OEM. This product ensures a good protection in the automatic gearbox and ensures smooth shifting. It significantly increases the lifetime of the transmission.



GRADE	METHOD	UNIT	VALUE
Colour	Visual		
Density @ 15 °C	ASTM D4052	kg/l	0,845
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	
Viscosity Index	ASTM D2270		153
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-48
Flash point	ASTM D92	°C	202
CCS viscosity @ -40 °C	ASTM D5293	mPa.s	

All data on this technical data sheet is indicative only.

Specifications

- ▷ AML 4G4319A509
- ▷ BENTLEY PY112995PA
- ▷ BMW 83220142516
- ▷ BMW M-1375.4
- ▷ HYUNDAI 040000C90SG
- ▷ JAGUAR FLUID 8432
- ▷ LAND ROVER TYK500050
- ▷ MASERATI 231603
- ▷ VW G 055 005
- ▷ ZF TE-ML 11