

# AUTOMATIC TRANSMISSION FLUIDS



**MOLINOL®**  
PREMIUM GERMAN LUBRICANTS

33/FG

140701701

## MOLINOL ATF 33/FG

This is a high-quality automatic transmission fluid that is specifically formulated for FORD-transmissions (Glide). This product is formulated in a way that it provides excellent anti-wear and anti-foam properties. Also, it reduces

the deposit formation to an absolute minimum which increases the operating lifetime of the transmission. An excellent automatic transmission fluid for FORD automatic transmissions.



GRADE	METHOD	UNIT	VALUE
Colour	Visual		
Density @ 15 °C	ASTM D4052	kg/l	0,869
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	
Viscosity Index	ASTM D2270		173
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	206
CCS viscosity @ -40 °C	ASTM D5293	mPa.s	

*All data on this technical data sheet is indicative only.*

## Specifications

- ▷ FORD ESP-M2C33-G
- ▷ FORD ESW-M2C33-F
- ▷ JD JDM J21A
- ▷ SQM2-9007-AA
- ▷ VOLVO 97330