

AUTOMATIC TRANSMISSION FLUIDS



MOLINOL®
PREMIUM GERMAN LUBRICANTS

A/A

140701801

MOLINOL ATF A/A

This is a very in depth formulated automatic transmission fluid that is based on solvent-refined oils. This product can only be used in automatic and semi-automatic gearboxes, power steering where ATF Type A Suffix A oil is

prescribed. The high viscosity index and low pour point of this product ensure optimal performance in a very broad temperature range.



GRADE	METHOD	UNIT	VALUE
Colour	Visual		
Density @ 15 °C	ASTM D4052	kg/l	0,857
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	
Viscosity Index	ASTM D2270		161
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	1,5
Pour point	ASTM D6892	°C	-42
Flash point	ASTM D92	°C	198
CCS viscosity @ -40 °C	ASTM D5293	mPa.s	36,7

All data on this technical data sheet is indicative only.

Specifications

- ▷ ALLISON C3
- ▷ ATF DEXRON B
- ▷ ATF TYPE A, SUFFIX A
- ▷ FORD M2C41-A
- ▷ FORD M2C41-B
- ▷ MB 236.2