

AUTOMATIC TRANSMISSION FLUIDS



MOLINOL®
PREMIUM GERMAN LUBRICANTS

LL

140702101

MOLINOL ATF LL

This is a full synthetic long-life automatic transmission fluid that is formulated with an exceptionally high viscosity index. Special Friction additives have been added to ensure low noise and smooth switching properties. This product is

neutral to synthetic seals and can be used in automatic transmissions of all kinds of vehicles like passenger cars, small vans and trucks.



GRADE	METHOD	UNIT	VALUE
Colour	Visual		
Density @ 15 °C	ASTM D4052	kg/l	0,843
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	
Viscosity Index	ASTM D2270		192
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	
Pour point	ASTM D6892	°C	-54
Flash point	ASTM D92	°C	214
CCS viscosity @ -40 °C	ASTM D5293	mPa.s	35,5

All data on this technical data sheet is indicative only.

Specifications

- ▷ ALLISON C4
- ▷ ALLISON TES-389
- ▷ CATERPILLAR TO-2
- ▷ FORD 166-H
- ▷ FORD M2C139-CJ
- ▷ FORD MERCON
- ▷ GM DEXRON II-D
- ▷ GM DEXRON II-E
- ▷ GM DEXRON III-F
- ▷ GM DEXRON III-G
- ▷ GM DEXRON III-H
- ▷ MAN 339 TYP V1
- ▷ MAN 339 TYP V2
- ▷ MAN 339 TYP Z1
- ▷ MAN 339 TYP Z2
- ▷ MB 236.1
- ▷ MB 236.10
- ▷ MB 236.5
- ▷ MB 236.6
- ▷ MB 236.7